

ALEXO®

Design icon for 90 years



**Glatz** 

# ALEXO®




## Material and technology

- Frame:** 10 struts made of varnished ash, pole diameter 30 mm, Alexo ribbed gear joint made of nickel-plated brass; rails of fibreglass
- Frame material:** ash, clear finish
- Frame shape:** round
- Shade cover:** available in material class 5 (100 % polyacrylic approx. 300 g/m<sup>2</sup>) or material class 4 (100 % polyester approx. 250 g/m<sup>2</sup>)
- Flounce:** available with or without flounce. The model without flounce is equipped with leather reinforcements.
- Protective cover:** optional
- Note:** Wood is a natural product and should not be left in the rain for too long!



Application



Fixations



## Assortment

Nominal size	Lateral distance	Pole Ø	Area covered	Height closed/ with flounce	Clear headroom/ with flounce	Total height	Foundation	Minimum weight for base	max. wind speed open perm.	Order no. Frame ash
cm	cm	cm	m <sup>2</sup>	cm	cm	cm	cm	kg	km/h (wind force)	
A	AS	M	B	E <sup>1</sup> /E <sup>2</sup>	F <sup>1</sup> /F <sup>2</sup>	G	C			
○ without flounce										
Ø 200 <sup>10</sup>	190	3.0	2.9	135 / 125	215 / 200	245	40×40	30	20 (4)	180 00 200 751
Ø 220 <sup>10</sup>	210	3.0	3.6	125 / 115	210 / 195	245	40×40	30	20 (4)	180 00 220 751
○ with flounce										
Ø 200 <sup>10</sup>	190	3.0	2.9	135 / 125	215 / 200	245	40×40	30	20 (4)	180 00 200 750
Ø 220 <sup>10</sup>	210	3.0	3.6	125 / 115	210 / 195	245	40×40	30	20 (4)	180 00 220 750


<sup>10</sup> 10 parts

The listed measures represent extrapolated average values that may be slightly different on the product (± 2% ± 5 cm).


The measures of the height are determined by the ST ground socket. If one of the offered bases is used, these measures change only slightly. Apart from the steel base minus 5 cm.

The max. wind speed limits as per our separate sheet apply only if the parasol canopy is in a horizontal position and if there is a fix ground anchorage.

In the presence of several parasols, the minimum distance between one parasol and another and between parasols and walls shall be 20 cm.



Loose cover max. 10 cm, concrete thickness min. 30 cm (pay attention to frost depth), Guarantee water drainage



10 parts

## Accessories

Fixing option ST (support tube ST <b>absolutely</b> necessary)		Order no.
1	Ground socket ST, galvanised steel	350 01 205 105
2	Support tube ST, Ø 25 – 33mm, galvanised steel	350 01 205 100
Fixing option Z (support tube Z <b>absolutely</b> necessary)		
3	Concrete base Z, 30 kg, Ø 47×8.5 cm	350 01 109 532
3	Concrete base Z, 40 kg, Ø 60×8.5 cm	350 01 109 529
4	<sup>3</sup> Granite base Z 40 kg, 45×45×8 cm, natural stone, with castors and retractable handle	350 01 109 465
4	<sup>3</sup> Granite base Z 55 kg, 55×55×9 cm, natural stone, with castors and retractable handle	350 01 109 445
5	Steel base Z 40 kg, 58.5×58.5×2 cm, galvanised steel	350 01 100 210
6	Wall bracket Z, 180 mm, galvanised steel	350 01 205 000
7	Lawn spike Z, 85×150×350, galvanised steel	350 01 205 400
8	Support tube Z, Ø 25 – 33mm, galvanised steel	350 01 200 135
Protective cover made of coated, tear-resistant polyester fabric		
9	Protective cover	350 01 609 983
Miscellaneous items		
10	OSYRION Spot LED battery-powered light, set of 2, with remote control, including charger	350 01 563 000
11	OSYRION Spot LED battery-powered light, set of 4, with remote control, including charger	350 01 563 100

<sup>3</sup> only suitable for smooth, joint free surface coverings





Glatz AG  
Parasols  
2022 Season

[glatz.com](https://www.glatz.com)

